


Delivery Premium Quality Fans Globally for Healthier Breathing

World's Largest Selection of Fan Products
World's Most Comprehensive Fan Solutions



Ningbo Longwell Electric Technology Co., Ltd

Headquarter: NO.100, South of Xuxiang River, Yuyao, Zhejiang Province, China 315400

Tell: +86 574 6218 9863

Fax: +86 574 6218 9863

Phone: 0086 183 5827 4663

Web: www.longwellfans.com | www.longwell-group.com | www.longwell-media.com

Email: sales@zjlongwell.com



LONGWELL TECHNOLOGY

**"Born for High-Quality Breathing
LONGWELL Fans Power Your Equipments"**



**Professional Manufacturer
of HVACR Fan & Motors**

—— EC Fan with Bracket

Longwell Group

Longwell-China

Longwell-USA

Longwell-Russia

Longwell-Europe

CATALOGUE

01-02

About Longwell

03-04

Testing and Standards

05-06

Mainly Application

07

Type Code

08-44


EC Fan with Bracket($\Phi 133$ - $\Phi 250$)

45-92

EC Fan with Bracket($\Phi 280$ - $\Phi 355$)

93-146

EC Fan with Bracket($\Phi 400$ - $\Phi 630$)



About Longwell

Born for High-Quality Breathing, LONGWELL Fans Power Your Equipment

OEM for Well-Known Brands

Supplies Fortune 500 Companies

Global Technical Support

LONGWELL is a leading fan manufacturer, specializing in high-quality fans, blowers, motors, and components for heating, ventilation, air conditioning, and refrigeration applications. We have a strong presence in delivery capabilities, design and R&D capabilities, as well as manufacturing, placing us at the forefront of the industry.

Our product range includes EC/DC/AC centrifugal fans, axial fans, AC/BLDC cross-flow fans, single/double forward curved fans, AC/BLDC/ECM motors, and industrial fan blowers. Since our establishment in 1990, we have continuously upgraded our facilities and production capacity, boasting advanced testing labs and production facilities with an annual capacity of millions of fans. With over 20 years of experience, we are highly skilled in the design, development, and manufacture of fans and motors. We export to over 30 countries and serve numerous Fortune 500 clients.

Our facilities and products are compliant with certifications such as ISO9001, ISO14001, BSCI, CE, UL/ETL, CCC, EMC, and LVD. These certifications demonstrate our compliance in quality management, environmental management, social responsibility, and product safety. We are quality-oriented and dedicated to providing products and services that meet international standards. 

Equipped with advanced testing labs and production facilities, including a B&K noise lab, CFD simulation lab, air dynamics test chambers, automatic welding machines, CNC machining centers, and auto robot injection machines, we ensure efficient production and on-time delivery.

As industry leaders, we prioritize technological innovation and efficiency. We employ advanced technologies such as aerodynamics principles and CFD simulation to ensure precise and efficient fan designs. Additionally, we offer customized services to design and manufacture fan systems according to specific customer requirements. Our focus is on providing high-tech, high-efficiency products that meet our customers' needs and contribute to a better future.

At LONGWELL, innovation is at the core of our operations, driving continuous improvement. With our extensive experience and expertise, we can quickly customize solutions that meet customer needs. We emphasize technological sophistication, utilizing advanced technologies and high-performance materials to deliver products that are efficient, safe, and reliable. Our brand is widely recognized globally, and we are committed to promoting sustainable development and advancing the efficient fan industry.

LONGWELL looks forward to collaborating with you and providing high-quality customized fan and motor solutions. Please feel free to contact us as we work together to create a brighter future.

193

Staff

40000m²

Floor Space

500⁺

Branding Clients

1Million⁺ PCS

Annual Outputs

6


Overseas offices
on spot support

50⁺


Members
R&D Team




B&K Noise Testing Lab



Production Line



Automatic Welding



Balance Machine



Automatic Welding Machine



Production Line - Centrifugal Fan



Automatic CNC machine



Air Dynamic Test Lab



Production Line - Axial Fans



Production Line

Testing and Standards

- ISO GB/T 19001-2016 idt ISO 9001:2015/GB/T 24001-2016 idt ISO 14001:2015/GB/T 45001-2020 idt ISO 45001:2018
- UL 507:2017 Ed.10+R:27/CSA C22.2#113:2018 Ed.11
- BSCI ANSI C63.4:2014/ANSI C63.4a-2017
- EN IEC 55014-1:2021/EN IEC 55014-2:2021/EN IEC 61000-3-2:2019 +A1:2021
EN 61000-3-3:2013 +A1:2019 +A2:2021 +AC:2022-01
EN 60335-2-80:2003 +A1:2004 +A2:2009;
EN 60335-1:2012 +A11:2014 +A13:2017 +A1:2019+A14:2019 +A2:2019+A15:2021
EN 62321-1:2013/EN 62321-2:2014/EN 62321-3-1:2014
EN 62321-4:2014+A1:2017/EN 62321-5:2014/EN 62321-6:2015
EN 62321-7-1:2015/EN 62321-7-2:2017/EN 62321-8:2017




Enterprise Credit Evaluation Certificate - Highest Level in China




Own-Brand



Own-Brand




ETL




ETL



CE



RoHS




CE



CE




CE




RoHS




ETL



ETL



ETL



CE



CE



ISO 9001




ISO 9001



RoHS




RoHS



RoHS



RoHS




RoHS



CE




CE




CE

Mainly Application


AHU/FCU/FFU/Air Purifier/ Sterilization Equipments/
Humidiifier equipments/EC Fan Grid (Wall)



Ventilation Unit Project




FFU(Fan Filter Unit) Project



Data Center Cooling Project



Ventilation Equipments Project



FFU(Fan Filter Unit) Project

Type Code

LW B E 3G 133 - 072 P S - 06

Series number

T-380VAC S-230VAC U-115V
L-12VDC M-24VDC
H-48VDC Z-310VDC

N-Without housing/bracket
S-Single inlet with housing
D-Dual-inlet with housing
P-with bracket

Diameter of Rotor:072/092/102/138/188/218

Diameter of Impeller

2E-2pole 4E-4pole 6E-6 pole 6D-6pole
8D-8pole 3G-3 phase 1G-Single phase

A-AC D-DC E-EC

B-Backward F-Forward

LW-Longwell

EC Fan with Bracket

Professional HVAC Fan & Motors Manufacturer



LWBE-133 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G133-072PS-06	230	72	/	473	609	5220	/



LWBE3G133-072NS-06 (without bracket)



LWBE3G133-072PS-06 (with bracket)



LWBE-155 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G155-072PS-01	230	40	0.3	433	371	3570	63



LWBE3G155-072NS-02 (without bracket)



LWBE3G155-072PS-01 (with bracket)



LWBE-175 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G175-072PS-10	230	132	0.6	924	893	5020	/



LWBE3G175-072NS-10 (without bracket)



LWBE3G175-072PS-10 (with bracket)



LWBE-190 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G190-072PS-12	230	104	1.16	851	798	4230	70



LWBE3G190-072NS-16 (without bracket)



LWBE3G190-072PS-12 (with bracket)



LWBE-220 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: B
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G220-072PS-10	230	75	0.6	886	433	2600	71



LWBE3G220-072NS-11 (without bracket)



LWBE3G220-072PS-10 (with bracket)



LWBE-220 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: B
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G220-092PS-11	230	145	1	989	711	3310	75



LWBE3G220-092NS-10 (without bracket)



LWBE3G220-092PS-11 (with bracket)



LWBE-225 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: B
- Operation Temperature: -25°C ~ +60°C
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G225-072PS-11	230	80	0.6	1112	433	2500	69



LWBE3G225-072NS-10 (without bracket)



LWBE3G225-072PS-11 (with bracket)



LWBE-225 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G225-092PS-12	230	170	1.4	1528	683	3060	71.1



LWBE3G225-092NS-11 (without bracket)




LWBE3G225-092PS-12 (with bracket)



LWBE-225 Serise


Product Characteristic

- | | |
|--------------------------|---|
| ● Impeller Material: | Plastic PA66 |
| ● Supply Voltage: | 230V/115V,50/60Hz |
| ● Mode of Operation: | S1 |
| ● Protection Class: | IP44 |
| ● Insulation Class: | B |
| ● Operation Temperature: | -25℃ ~ +60℃ |
| ● Technical Feature: | Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection. |
- 




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G225-092PS-13	230	160	1.1	1545	731	3000	71



LWBE3G225-092NS-12 (without bracket)



LWBE3G225-092PS-13 (with bracket)



LWBE-225 Serise


Product Characteristic

- Impeller Material: PA6+GF
- Supply Voltage: 230V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G225-092PS-07	230	315	1.87	1630	839	3500	71



LWBE3G225-092NS-13 (without bracket)



LWBE3G225-092PS-07 (with bracket)



LWBE-250 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: B
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G250-072PS-15	230	90	0.8	1215	391	2150	68



LWBE3G250-072NS-29 (without bracket)



LWBE3G250-072PS-15 (with bracket)



LWBE-250 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G250-092PS-16	230	140	0.6	1531	785	3010	72.1



LWBE3G250-092NS-12 (without bracket)



LWBE3G250-092PS-16 (with bracket)



LWBE-250 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G250-072PS-17	230	140	1.1	1421	639	2760	77



LWBE3G250-072NS-21 (without bracket)



LWBE3G250-072PS-17 (with bracket)



LWBE-250 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: B
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G250-092PS-20	230	145	1	1730	525	2500	74



LWBE3G250-092NS-22 (without bracket)



LWBE3G250-092PS-20 (with bracket)



LWBE-250 Serise


Product Characteristic

- Impeller Material: Plastic PA66
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: B
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G250-092PS-21	230	170	1.1	1421	556	2600	69



LWBE3G250-092NS-23 (without bracket)



LWBE3G250-092PS-21 (with bracket)



LWBE-250 Serise


Product Characteristic

- Impeller Material: Galvanised sheet steel
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G250-102PS-22	230	240	1.6	1524	773	3150	78



LWBE3G250-102NS-24 (without bracket)



LWBE3G250-102PS-22 (with bracket)



LWBE-250 Serie


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: B
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G250-102PS-23	230	270	1.2	1751	824	3170	84



LWBE3G250-102NS-25 (without bracket)



LWBE3G250-102PS-23 (with bracket)



LWBE-250 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G250-102PS-24	230	370	2.6	1700	1082	3500	82



LWBE3G250-102NS-26 (without bracket)



LWBE3G250-102PS-24 (with bracket)



LWBE-280 Serise


Product Characteristic

- Impeller Material: Galvanised sheet steel
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G280-092PS-15	230	165	1.25	1813	680	2600	74



LWBE3G280-092NS-12 (without bracket)



LWBE3G280-092PS-15 (with bracket)



LWBE-280 Serise


Product Characteristic

- Impeller Material: Galvanised sheet steel
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G280-092PS-13	230	180	1.35	2019	546	2200	72



LWBE3G280-092NS-17 (without bracket)



LWBE3G280-092PS-13 (with bracket)



LWBE-280 Serise


Product Characteristic

- Impeller Material: Galvanised sheet steel
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G280-092PS-14	230	105	0.86	1743	481	2200	/



LWBE3G280-092NS-13 (without bracket)



LWBE3G280-092PS-14 (with bracket)



LWBE-280 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G280-102PS-16	230	340	2.3	2318	824	2760	78



LWBE3G280-102NS-14 (without bracket)



LWBE3G280-102PS-16 (with bracket)



LWBE-280 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G280-102PS-18	230	475	3.1	2472	1051	3100	82



LWBE3G280-102NS-15 (without bracket)



LWBE3G280-102PS-18 (with bracket)



LWBE-280 Serise


Product Characteristic

- Impeller Material: Galvanised sheet steel
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G280-102PS-19	230	625	4	3039	1102	3000	82



LWBE3G280-102NS-19 (without bracket)



LWBE3G280-102PS-19 (with bracket)



LWBE-280 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G280-138PT-05	400	860	1.22	3028	886	3000	85



LWBE3G280-138NT-03 (without bracket)



LWBE3G280-138PT-05 (with bracket)



LWBE-280 Serie


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G280-138PT-06	400	1355	1.9	3790	1421	3500	89



LWBE3G280-138NT-18 (without bracket)



LWBE3G280-138PT-06 (with bracket)



LWBE-310 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G310-092PS-12	230	150	1.2	2410	443	1750	75



LWBE3G310-092NS-17 (without bracket)



LWBE3G310-092PS-12 (with bracket)



LWBE-310 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G310-092PS-11	230	160	1.25	2235	474	1850	75



LWBE3G310-92NS-20 (without bracket)



LWBE3G310-92PS-11 (with bracket)



LWBE-310 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G310-102PS-02	230	285	1.57	2869	630	2150	70



LWBE3G310-102NS-16 (without bracket)



LWBE3G310-102PS-02 (with bracket)



LWBE-310 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G310-102PS-15	230	370	2.6	2936	700	2300	76



LWBE3G310-102NS-19 (without bracket)



LWBE3G310-102PS-15 (with bracket)



LWBE-310 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G310-102PS-16	230	450	3	2884	963	2600	78



LWBE3G310-102NS-18 (without bracket)



LWBE3G310-102PS-16 (with bracket)



LWBE-310 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G310-138PT-04	400	980	1.64	4398	824	2600	74



LWBE3G310-138NT-05 (without bracket)



LWBE3G310-138PT-04 (with bracket)



LWBE-310 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G310-138PT-10	400	1588	2.4	5593	1082	3300	92



LWBE3G310-138NT-25 (without bracket)



LWBE3G310-138PT-10 (with bracket)



LWBE-355 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: B
- Operation Temperature: -25°C ~ +60°C
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G355-092PS-15	230	120	0.9	2472	350	1400	68



LWBE3G355-092NS-19 (without bracket)



LWBE3G355-092PS-15 (with bracket)



LWBE-355 Serie


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25°C ~ +60°C
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G355-102PS-16	230	285	2	3554	618	1800	76



LWBE3G355-102NS-20 (without bracket)



LWBE3G355-102PS-16 (with bracket)



LWBE-355 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: B
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G355-102PS-17	230	330	1.5	3142	670	1900	77



LWBE3G355-102NS-21 (without bracket)



LWBE3G355-102PS-17 (with bracket)



LWBE-355 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V/115V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G355-102PS-18	230	423	5.3	3915	770	2050	/



LWBE3G355-102NS-15 (without bracket)



LWBE3G355-102PS-18 (with bracket)



LWBE-355 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM,Tach output,Locked-Rotor protection,Reverse Polarity Over-voltage protection,Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G355-138PT-20	400	990	1.63	5356	639	2100	79



LWBE3G355-138NT-17 (without bracket)



LWBE3G355-138PT-20 (with bracket)



LWBE-355 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G355-138PT-12	400	1100	3.6	6249	1353	2710	77



LWBE3G355-138NT-27 (without bracket)



LWBE3G355-138PT-12 (with bracket)



LWBE-355 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G355-138PT-05	400	1700	2.8	7045	830	2700	81



LWBE3G355-138NT-12 (without bracket)



LWBE3G355-138PT-05 (with bracket)



LWBE-355 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G355-188PT-11	400	3090	4.2	8034	1545	3200	96



LWBE3G355-188NT-26 (without bracket)



LWBE3G355-188PT-11 (with bracket)



LWBE-355 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 380V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G355-188PT-26	380	3100	5.2	6756	2524	3800	96



LWBE3G355-188NT-29 (without bracket)



LWBE3G355-188PT-26 (with bracket)



LWBE-400 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G400-102PS-09	230	297	/	4463	420	1250	/



LWBE3G400-102NS-14 (without bracket)



LWBE3G400-102PS-09 (with bracket)



LWBE-400 Serise


Product Characteristic

- | | |
|--------------------------|---|
| ● Impeller Material: | Aluminum Alloy |
| ● Supply Voltage: | 230V,50/60Hz |
| ● Mode of Operation: | S1 |
| ● Protection Class: | IP44 |
| ● Insulation Class: | F |
| ● Operation Temperature: | -25℃ ~ +60℃ |
| ● Technical Feature: | Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection. |
- 




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G400-102PS-11	230	300	2.1	3554	546	1460	76



LWBE3G400-102NS-16 (without bracket)



LWBE3G400-102PS-11 (with bracket)



LWBE-400 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: B
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G400-102PS-01	230	330	1.5	3914	556	1430	70



LWBE3G400-102NS-02 (without bracket)



LWBE3G400-102PS-01 (with bracket)



LWBE-400 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 230V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G400-102PS-10	230	500	3.6	5615	622	1520	/



LWBE3G400-102NS-15 (without bracket)



LWBE3G400-102PS-10 (with bracket)



LWBE-400 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM,Tach output,Locked-Rotor protection,Reverse Polarity Over-voltage protection,Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G400-138PT-04	400	1100	2.4	7459	840	2060	/



LWBE3G400-138NT-12 (without bracket)



LWBE3G400-138PT-04 (with bracket)



LWBE-400 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G400-188PT-07	400	2060	4.2	9682	1627	2650	84



LWBE3G400-188NT-17 (without bracket)



LWBE3G400-188PT-07 (with bracket)



LWBE-450 Serise


Product Characteristic

- | | |
|--------------------------|---|
| ● Impeller Material: | Aluminum Alloy |
| ● Supply Voltage: | 400V,50/60Hz |
| ● Mode of Operation: | S1 |
| ● Protection Class: | IP54 |
| ● Insulation Class: | F |
| ● Operation Temperature: | -25℃ ~ +60℃ |
| ● Technical Feature: | Control input 0-10VDC/PWM,Tach output,Locked-Rotor protection,Reverse Polarity Over-voltage protection,Soft Start Protection. |
- 




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G450-138PT-12	400	386	/	5329	452	1200	/



LWBE3G450-138NT-11 (without bracket)



LWBE3G450-138PT-12 (with bracket)



LWBE-450 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G450-138PT-13	400	900	/	7182	730	1610	/



LWBE3G450-138NT-12 (without bracket)



LWBE3G450-138PT-13 (with bracket)



LWBE-450 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G450-138PT-04	400	910	3.4	7828	824	1720	/



LWBE3G450-138NT-08 (without bracket)



LWBE3G450-138PT-04 (with bracket)



LWBE-450 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G450-188PT-07	400	1590	3.45	7425	1568	2400	/



LWBE3G450-188NT-15 (without bracket)



LWBE3G450-188PT-07 (with bracket)



LWBE-450 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G450-188PT-08	400	2060	4.2	8019	1802	2600	/



LWBE3G450-188NT-16 (without bracket)



LWBE3G450-188PT-08 (with bracket)



LWBE-450 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM,Tach output,Locked-Rotor protection,Reverse Polarity Over-voltage protection,Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G450-188PT-16	400	2400	5.2	8985	840	2600	/



LWBE3G450-188NT-14 (without bracket)



LWBE3G450-188PT-16 (with bracket)



LWBE-450 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G450-188PT-09	400	2595	5.3	8661	2114	2800	/



LWBE3G450-188NT-17 (without bracket)



LWBE3G450-188PT-09 (with bracket)



LWBE-500 Serise

Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP44
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications



Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G500-138PT-08	400	870	1.46	8137	464	1100	71



LWBE3G500-138NT-13 (without bracket)



LWBE3G500-138PT-08 (with bracket)



LWBE-500 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃~+60℃
- Technical Feature: Control input 0-10VDC/PWM,Tach output,Locked-Rotor protection,Reverse Polarity Over-voltage protection,Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G500-188PT-07	400	1900	4.0	10305	903	1705	/



LWBE3G500-188NT-14 (without bracket)



LWBE3G500-188PT-07 (with bracket)



LWBE-500 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G500-188PT-04	400	3000	4.95	14214	886	1800	89



LWBE3G500-188NT-08 (without bracket)



LWBE3G500-188PT-04 (with bracket)



LWBE-500 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G500-188PT-02	400	3160	6.5	12243	1265	2000	/



LWBE3G500-188NT-09 (without bracket)



LWBE3G500-188PT-02 (with bracket)



LWBE-500 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G500-188PT-05	400	4200	9.0	13472	1541	2200	/



LWBE3G500-188NT-10 (without bracket)



LWBE3G500-188PT-05 (with bracket)



LWBE-560 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G560-188PT-02	400	2770	4.4	16480	886	1520	81



LWBE3G560-188NT-09 (without bracket)



LWBE3G560-188PT-02 (with bracket)



LWBE-560 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G560-188PT-03	400	2420	5.3	14879	1013	1500	/



LWBE3G560-188NT-10 (without bracket)



LWBE3G560-188PT-03 (with bracket)



LWBE-560 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G560-188PT-01	400	3300	8	16039	1166	1610	/



LWBE3G560-188NT-01 (without bracket)



LWBE3G560-188PT-01 (with bracket)



LWBE-560 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 380V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G560-188PT-08	380	4700	7.9	19760	1545	1850	91



LWBE3G560-188NT-14 (without bracket)



LWBE3G560-188PT-08 (with bracket)



LWBE-560 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G560-218PT-06	400	5600	9.5	23896	1442	1800	/



LWBE3G560-218NT-13 (without bracket)



LWBE3G560-218PT-06 (with bracket)



LWBE-630 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G630-188PT-01	400	2195	4.8	19247	887	1300	/



LWBE3G630-188NT-06 (without bracket)



LWBE3G630-188PT-01 (with bracket)



LWBE-630 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G630-188PT-02	400	2955	6.5	21100	1071	1380	/



LWBE3G630-188NT-07 (without bracket)



LWBE3G630-188PT-02 (with bracket)



LWBE-630 Serise


Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




Technical Specifications


Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G630-188PT-04	400	5600	8.1	21742	1677	1780	/



LWBE3G630-188NT-09 (without bracket)



LWBE3G630-188PT-04 (with bracket)




LWBE-630 Serise

Product Characteristic

- Impeller Material: Aluminum Alloy
- Supply Voltage: 400V,50/60Hz
- Mode of Operation: S1
- Protection Class: IP54
- Insulation Class: F
- Operation Temperature: -25℃ ~ +60℃
- Technical Feature: Control input 0-10VDC/PWM, Tach output, Locked-Rotor protection, Reverse Polarity Over-voltage protection, Soft Start Protection.




LWBE3G630-188NT-10 (without bracket)



Technical Specifications

Model	Voltage (V)	Input Power (W)	Current (A)	Air Volume (m³/h)	Static Pressure (Pa)	Speed (RPM)	Noise [dB(A)]
LWBE3G630-188PT-05	400	3600	4.4	19158	968	1250	/



LWBE3G630-188PT-05 (with bracket)

